Index

CCTV

Professional Cameras
Professional Cameras

Monocrome Cameras
Colour Cameras
Day / Night Cameras
Specialised Cameras
Specialised Cameras

Covert Cameras
Bullet Cameras
PIR Cameras
Indoor Mini Dome Cameras
Anti-Vandal Dome
TCP/IP Cameras
With Built-in varifocal lens
High Speed Camera Domes
Lenses - Vari-focal Direct Drive
Lenses - Vari-focal Direct Drive

Varifocal & Manual Zoom Video Lens
Varifocal Direct Drive
Monitors
Monitors

Colour
TFT LCD
Sequintial Switches
Sequintial Switches

Video Recorders / Multiplexers
Video Recorders / Multiplexers

Embedded Digital Video Recorders
PC-Based Digital Video Recorders
Plug & Play Video Capture Cards
Mobile Digital video Recording
Quad Display Units
Quad Display Units

Video Amplifier
Video Amplifier

Twisted pair Cable Transmission
Twisted pair Cable Transmission

Web Transmitters / Receivers / Decoder
Web Transmitters / Receivers / Decoder

Hardware & Accessories
Hardware & Accessories

Camera Brackets
Camera Housings
Lighting Protection
Visual Verification
Visual Verification

Monocrome Cameras

SHANY

MTC-2301 - 1/3" Monochrome Camera

- High-Sensitivity of 0.05 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC
- Ordering no. 73MTC-2301

MTC-2302 - B/W Camera

- 600 TVL
- High-Sensitivity of 0.05 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC
- Ordering no. 73MTC-2302

Colour Cameras

SHANY

MTC-7351 - Colour Box Camera

- SONY Super-HAD CCD
- 420 TVL
- High-sensitivity of 0.2 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC

- Ordering no. 73MTC-7351

MTC-9352HQ - 1/3" High Resolution Colour Camera

- SONY Super-HAD CCD
- 540 TVL
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC
- Ordering no. 73MTC-9352HQ

Day / Night Cameras

SAMSUNG

SCC- B2391P - 1/3" High Resolution Low Light Day/Night Camera with WDR

- 540 TVL Colour
- 0.3Lux (0.002 Sense Up) Colour
- 0.06Lux (0.0004 Sense Up) Monochrome
- Digital Signal processor (DSP)
- Back Light Compensation (BLC)
- Electric Shutter Control (ESC)
- Direct Current (DC)& Video Iris
- AC24V/12V
- Ordering no. 61SCC-B2391P

SCC-B2307P - 1/3" High Resolution Low Light Exview Day/Night Camera

- 500 TVL
- 0.2Lux (0.001 Sense Up) Colour
- 0.03Lux (0.0002 Sense Up) Monochrome
- Digital Signal processor (DSP)
- Back Light Compensation (BLC)
- Direct Current (DC) & Video Iris
- On Screen Display (OSD) Set-up
- AC24V/12V
- Ordering no. 61SCC-2307P

SCC-B2311P - 1/3" High Resolution Low Light Day/Night Camera

- Software Day / Night
- 540 TVL
- 0.12Lux (0.0009 Sense Up) Colour
- 0.12Lux (0.0009 Sense Up) Monochrome
- Digital Signal processor (DSP)
- Electric Shutter Control (ESC)
- Direct Current (DC)& Video Iris
- AC 24V/12 V
- Ordering no. 61SCC-B2311P

SCC-B2313P - 1/3" High Resolution Low Light Day/Night Camera

- 540 TVL
- 0.12Lux (0.0009 Sense Up) Colour
- 012Lux (0.00009 Sense Up) Monochrome
- Digital Signal processor (DSP)
- Back Light Compensation (BLC)
- Direct Current (DC) & Video Iris
- On Screen Display (OSD) Set-up
- AC 24V/12 V
- Ordering no. 61SCC-2313P

SCC-B2315P - 1/3" High Resolution Low Light Day/Night Camera with WDR

- 540 TVL
- 0.12Lux (0.0009 Sense Up) Colour
- 0.012Lux (0.00009 Sense Up) Monochrome
- Digital Signal processor (DSP)
- Back Light Compensation (BLC)
- Direct Current (DC) & Video Iris
- On Screen Display (OSD) Set-up
- AC 24V/12 V
- Ordering no. 61SCC-B2315P

SHANY

MTC-IR7351 - 1/3" IR Sensitive Colour Camera

- SONY CCD
- 420 TVL
- Sensitivity of 0.2 Lux at F1.2 (0.001 Lux with IR Illumination)
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC
- Ordering no. 73MTC-7351

MTC-MIR8362HQDN - 1/3" High Resolution Day/Night Camera

- SONY Super-HAD CCD
- 540 TVL
- Moving IR Cut Filter
- Sensitivity of 0.15 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- Direct Current (DC) & Video Iris
- 12VDC/24VAC
- Ordering no. 73MTC-MIR8362HQDN

MTC-WD01 - Wide Dynamic Camera

- SONY Super-HAD CCD 520 TVL
- Sensitivity of 0.1 Lux (Colour)
- 0.002 Lux (B/W) at F1.2
- On Screen Display (OSD) Control
- AWB (ATW, AWC & Manual)
- Electric Shutter Control (ESC) (x 128, 1/50 ~ 1/20.000)
- Wide Dynamic Range (WDR)
- 4 x Privacy Zones
- Ordering no. 73MTC-WD01

Covert Cameras

SHANY

MTC-305 - 1/3" Side Viewing Colour Smoke Detector Camera

- 3.6mm lens
- 420 TVL
- 1.5Lux
- Electric Shutter Control (ESC) On
- 1.5Lux
- Electric Shutter Control (ESC) On
- c/w 12 VDC Power Supply

VISIONLINE

VC-B335P4A - 1/4" Colour Fixed Lens Mini Camera with Audio

- " 420 TVL
- Day / Night applications
- 12VDC
- Audio function
- Ordering no. 62VLC-B335P4A

VC-B355P4 - 1/4" Colour Fixed Lens Mini Camera with Audio

- 1/4" Colour Fixed Lens Mini Camera with Audio
- Day / Night applications
- 12VDC
- Audio Function
- Ordering no.62VLC-B335P4

VLC-380CCPIR - 1/4" Colour Fixed Lens Mini Camera

- 380 TVL
- Day / Night applications
- 12V Direct Current (DC)
- Ordering no. 55VLC-B380CCPIR

Bullet Cameras

VISIONLINE

CCD-325C - Navigator Colour Bullet Camera with Audio & built-in IR Illuminator

- Built-in IR illumination
- 6mm Lens
- 330TVL
- 0 Lux (10m IR On)
- Electric Shutter Control (ESC) (on)
- Built-in microphone
- Includes 10m connecting cable with RCA connector
- Includes 12VDC Power Supply
- Includes mounting bracket

- Ordering no. 57CCD-325C

VLC-380CPUIR - 1/4" Colour Bullet Camera with built-in IR Illuminator -

- 4mm Lens
- 380TVL
- 0.25 Lux (10 meter with IR On)
- Back Light Compensation (BLC) On
- Electric Shutter Control (ESC) On
- DC12V
- Includes Mounting Bracket
- 12 units IR LED
- Ordering no. 55VLC-380CPUIR

VLC-380MPUIR - 1/4" Monochrome Bullet Camera with built-in IR Illuminator -

- 4mm Lens
- 380TVL
- 0.25 Lux (10m IR on) at F2.0
- Back Light Compensation (BLC) On
- Electric Shutter Control (ESC) On
- 12VDC
- Includes Mounting Bracket
- Ordering no. 55VLC-380MPUIR

VLC-DNIR28 - 1/3" Day/Night Bullet Camera with built- in IR Illuminator

- Sony CCD 6mm lens
- 420 TVL
- Colour 0.8 Lux
- Colour 0.8 Lux
- Monochrome 0.1 Lux
- 12 VDC

- Automatic Gain Control (AGC)
- Includes mounting bracket
- Ordering no. 62VLC-DNIR28

VLC-DNIR28-3 - 1/3" Day/Night Bullet Camera with built-in IR Illuminator

- Sony CCD 3.6mm lens
- 420 TVL
- Colour 0.8 Lux
- Monochrome 0.1 Lux
- 12 VDC
- Includes Mounting Bracket
- Ordering no. 62VLC-DNIR28-3

VLC-DNIR63-V - 1/3" Day/Night Vari-focal Bullet Camera with built-in IR Illuminator

- Sony CCD 4-9mm lens
- 420 TVL
- Colour 0.8 Lux
- Monochrome 0.1 Lux
- 12 VDC
- 12VDC
- Includes mounting bracket
- Ordering no. 62VLC-DNIR63-V

PIR Cameras

VISIONLINE

VLC-380CCPIR - VisionLine 1/4" Colour Fixed Lens, working PIR Camera with Audio

- 3.6mm Lens
- 380 TVL
- 2 Lux
- BLC (On)
- ELC (On)

- DC12V
- Ordering no. 70VLC-380CCPIR

VLC-400MCPIR - VisionLine 1/4" Monochrome Fixed Lens, non working PIR Camera

- 3.6mm Lens
- 380 TVL
- 1 Lux
- BLC (On)
- ELC (On)
- DC12V
- Ordering no. 70VLC-400MCPIR

Indoor Mini Dome Cameras

SAMSUNG

SCC-B5311P - 1/3" High Resolution Day/Night Mini Dome Camera - 3.8mm Lens

- Software Day/ Night
- 3.8mm Lens
- 540 TVL
- 0.3 Lux (0.002 Sense Up) Colour
- 0.3 Lux (0.002 Sense Up) Monochrome
- Horizontal and vertical mirroring
- Digital Noise Reduction (DNR) On / Off
- 24VAC / 12VDC
- Ordering no.61SCC-B5311P

SCC-B5313P - 1/3" High Resolution Day/Night Mini Dome Camera with 3mm Lens

- Software Day/ Night
- 3mm Lens
- 540 TVL
- 0.3 Lux (0.002 Sense Up) Colour
- 0.3 Lux (0.002 Sense Up) Monochrome
- Horizontal and vertical mirroring
- Digital Noise Reduction (DNR) On / Off
- 24VAC / 12VDC
- Ordering no.61SCC-B5313P

SCC-B5315P - 1/3" High Resolution Day/Night Mini Dome Camera with 8mm Lens

- Software Day/ Night
- 8.0 mm Lens
- 540 TVL
- 0.3 Lux (0.002 Sense Up) Colour
- 0.3 Lux (0.002 Sense Up) Monochrome
- Horizontal and vertical mirroring
- Digital Noise Reduction (DNR) On / Off
- 24VAC / 12VDC
- Ordering no.61SCC-B5315P

SCC-B5352P - 1/3" High Resolution Day/Night (Electric) Mini Dome Camera with Vari-focal Lens

- Software Day / Night
- 2.5-6mm Lens
- 540 TVL
- 0.12 Lux (0.0009 Sense Up) Colour
- 0.12 Lux (0.0009 Sense Up) Monochrome
- Automatic Gain Control (AGC) On
- Electric Shutter Control (ESC) On
- 24 VAC / 12 VDC
- Ordering no. 61SCC-B5352P

SCC-B5353P - 1/3" High Resolution Day/Night (Moving Filter) Mini Dome Camera with Vari-focal Lens

- Moving Filter Day / Night
- 2.5-6mm Lens
- 540 TVL
- 0.12 Lux (0.0009 Sense Up) Colour
- 0.012 Lux (0.00009 Sense Up) Monochrome
- Back Light Compensation (BLC) On / Off
- Automatic Gain Control (AGC) On
- Electric Shutter Control (ESC) On
- 24 VAC / 12 VDC
- Ordering no. 61SCC-B5353P

SHANY

MTC-2438HQ - 1/3" High Resolution Colour Mini Dome Camera with Vari-focal Lens

- SONY Super-HAD CCD
- 540 TVL
- 3.8 ~ 9mm Auto Iris Lens with Level Adjust
- Sensitivity of 0.25 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- 12VDC
- Ordering no. 73MTC-2438HQ

MTC-805D - 1/3" High Resolution Colour Mini Dome Camera

- 1/3" High Resolution Colour Mini Dome Camera
- 420 TVL
- 3.6mm Lens
- Sensitivity of 0.3 Lux at F1.2
- Back Light Compensation (BLC) (On)
- Automatic Gain Control (AGC) (On)
- Electric Shutter Control (ESC) (On)
- 12VDC
- Ordering no. 73MTC-805D

MTC906D - Black and White Dome Camera

- SONY Super-HAD CCD
- 420 TVL
- 3.6mm Lens
- Sensitivity of 0.05 Lux at F1.2
- Back Light Compensation (BLC) (On)
- Automatic Gain Control (AGC) (On)
- Electric Shutter Control (ESC) (On)
- 12 VDC
- Ordering no. 73MTC-906D

VTP-20D - 1/3" Colour Indoor Mini Dome Camera

- SONY Super-HAD CCD
- 420 TVL
- 3.6mm Lens
- Sensitivity of 0.3 Lux at F1.2
- Back Light Compensation (BLC) (On)
- Automatic Gain Control (AGC) (On)
- Electric Shutter Control (ESC) (On)
- 12VDC
- Ordering no. 73VTP-20D

Anti-Vandal Dome

SAMSUNG

SCC B5392 - 1/3" Vandal Proof Mini Dome Day/Night Camera with Vari-focal Lens

- Software Day/Night
- 2.5-6mm Lens
- 540 TVL
- 3-Axis Design
- External impact protection
- Digital Noise Reduction (DNR)
- IP 66 Grade
- 24 VAC / 12 VDC
- Ordering no. 61SCC-B5392P

SCC-B5393P - 1/3" Vandal Proof Mini Dome Day/Night Camera with Vari-focal Lens

- Moving Filter Day/Night
- 2.5-6mm Lens
- 540 TVL
- 3-Axis Design
- External impact protection
- Digital Noise Reduction (DNR)
- IP 66 Grade
- 24 VAC / 12 VDC
- Ordering no. 61SCC-B5393P

VISIONLINE

MTC-5838HQ - 1/3" Vandal Proof Mini Dome Colour Camera with Vari-focal Lens

- SONY Super-HQ1 CCD
- 3-Axis
- 540 TVL
- 2.9mm-10mm Auto Iris Lens with Level Adjust
- Sensitivity of 0.25 Lux at F1.2
- 12VDC
- Flush mount
- IP66 Rating

- Ordering no. 73MTC-5838HQ

MTC-L405D - 1/3" Vandal Proof Dome for Vehicle

- Sony Medium Resolution CCD
- 420 TVL
- 4.3mm / F2
- Board lens
- 12 LEDs with 10m illuminating distance
- Automatic Gain Control (AGC)
- CDS Auto Control
- De-Vibration Control
- 12 VDC

MTC-L405DHQ - 1/3" Super High Resolution Vandal Proof Dome for Vehicle

- Sony Super High Resolution CCD
- 540 TVL
- 4.3mm / F2
- Board lens
- 12 LEDs with 10m illuminating distance
- Automatic Gain Control (AGC)
- CDS Auto Control
- De-Vibration Control
- 12 VDC

MTC-L5838HQ - 1/3" Vandal Proof Mini Dome Colour Camera with Vari-focal Lens

- SONY Super-HQ1 CCD
- 540 TVL
- 3-Axis
- Mech IR Cut Filter
- 2.9-10mm AI Lens with Level Adjustment

- Electric Shutter Control (ESC) On / Off
- 12VDC
- Flush mount
- IP66 Rating

TCP/IP Cameras

SAMSUNG

SCC-C6475P - IP WDR x22 High Speed PTZ Day/Night Dome Camera

- 1/4" Exview CCD
- Built-in 22x optical zoom lens
- 10x Digital Zoom
- Digital Signal processor (DSP)
- On Screen Display (OSD)Set-up
- Privacy Masking
- 360 degree endless pan (slip ring)
- AC 24V
- Ordering no. 61SCC-C6475P

SHANY

WTC-L675D - IP Camera with IR LEDs

- 1/3" SONY Super HAD CCD
- 420 TVL
- 24 LEDs at 2 Lux
- 0.4 Lux @ F2.0
- MPEG-4 Compression
- Two way audio

VISIONLINE

WTC-L675DHQ - High Resolution IP Camera with IR LEDs

- 1/3" SONY Super High Resolution HAD CCD
- 540 TVL
- 24 LEDs at 2 Lux
- 0.4 Lux @ F2.0
- MPEG-4 Compression
- Two way audio

With Built-in varifocal lens

SHANY

MTC-1338 - 1/3" Colour Camera with Built-in Vari-focal Lens

- SONY Super-HAD CCD
- 420 TVL
- 3.8 ~ 9.5mm Auto Iris Lens
- Sensitivity of 0.15 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- 12 VDC / 24 VAC
- Ordering no. 73MTC-1338

MTC-1438 - 1/3" High Resolution Colour Camera with built-in Vari-focal Lens

- SONY Super-HAD CCD
- 420 TVL
- 3.8 ~ 9.5mm Auto Iris Lens
- Sensitivity of 0.18 Lux at F1.2
- Back Light Compensation (BLC) (On/Off)
- Automatic Gain Control (AGC) (On/Off)
- Electric Shutter Control (ESC) (On/Off)
- 12 VDC/ 24 VAC
- Ordering no. 73MTC-1438

SAMSUNG

SADT-100CM - Ceiling Mountable Adaptor

- To be used with Wall Mount Bracket
- Ordering no. 61SADT-100CM

SADT-100PM - Pole Mount Adaptor

- To be used for installation of the wall mounted bracket on the cylindrical poles with a diameter greater
- Ordering no. 61SADT-100PM

SADT-100WM - Wall Mount Bracket

- To b used with indoor or outdoor pendant mount housing
- Ordering no.61SAT-100WM

SADT-110CM - Corner Mount Adaptor

- To be used for installation of the wall mounted bracket (WM) on the corner of a building or other stru
- Ordering no. 61SADT-110CM

SBR-100DCM - Indoor Flush-mount Suspended Ceiling Mounting Kit

- Solid structure
- Metallic material
- Ordering no. 61SBR-100DCM

SCC-641P - X22 High Speed Pan Tilt & Zoom Colour SmartDome Camera

- 1/4" Super HAD CCD
- 3.6 to 79.2mm Focal Length
- 10x Digital Zoom
- Possible to connect up to 256 cameras using the SSC-1000 controller
- RS-485 Control

SCC-643AP - X22 High Speed Pan Tilt & Zoom Day/Night Smart Dome Camera

- 1/4" Super HAD CCD
- 3.6 to 79.2mm Focal Length
- 10x Digital Zoom
- Possible to connect up to 256 cameras using the SSC-1000 controller
- RS-485 Control

SCC-643D - Smoked Lower Dome

- Camera c/w Clear Lower Dome
- Ordering no. 61SCC-643D

SCC-C6407P - X32 High Speed Pan Tilt & Zoom Day/Night Smart Dome Camera with WDR

- 1/4" Ex-View CCD
- 3.6 to 79.2mm Focal Length
- 320x Zoom Ration (32x Optical, 10x Digital)
- RS-485 Control
- Digital Signal processor (DSP)
- Motion Detection
- 4 x Alarm Input
- Privacy Masking
- Ordering no. 61SCC-C6407P

SHG-120 - Indoor Pendant Mount Housing

- For indoor use
- The place of installation should be able to bear up to 4 times the total product weigh
- Aluminum material
- Ordering no. 61SHG-220

SHG-220/EXP - Outdoor Pendant Mount Housing

- For outdoor installation
- Aluminum material
- Built-in fan/heater function
- Ordering no. 61SHG-220

SSC-1000P - 3-Axis Variable Speed System Controller

- Long range remote control (up to 1.2km) using RS-485
- Full control of the pan/tilt drive, the lens and the camera
- The camera receiver unit and DVR can be controlled with this system keyboard
- Up to 128 SmartDome cameras can be controlled at once
- Manipulation is easily done by using a joystick
- Multiple system controllers can be used (up to 8 units)
- Ordering no.61SSC-1000-P

SSC-2000P - 3-Axis Variable Speed System Controller

- Long range remote control (up to 1.2km) using RS-485
- The camera receiver unit and DVR can be controlled with this system keyboard
- A LCD is used to show the respective of system keyboard
- Systems can be controlled from different locations and a maximum of 32 units can be connected at th

- Menus can be selected conveniently through a touch screen function

---

Varifocal & Manual Zoom Video Lens

PENTAX

C6ZE - 12.5 to 75mm Manual Zoom Video Iris Lens, 1/3" Format

- F1.8 - 720
- CS Mount

H6ZBE - 8 to 48mm Manual Zoom Video Iris lens, 1/3" Format

- F1 - 720
- CS Mount

HS2V616E - 6 to 12mm Vari-focal Video Iris Lens, Day/Night, 1/2" Format

- F1.6 - 200
- CS Mount

TS2V214AE* - 2.8 to 6mm Vari-focal Video Iris Lens, Day/Night, 1/3" Format

- F1.4 - 200
- CS Mount
- *Please note that this product above may subject to 4 week lead time

TS3V310E - 3 to 8mm Vari-focal Video Iris, Day/Night Lens, 1/3" Format

- F1.4 - 300
- CS Mount
- Ordering no. 59TS3V310E

TS6ZE - 6.3 to 36mm Manual Zoom Video Iris lens, 1/3" Format

- F1.4 - 512
- CS Mount

Varifocal Direct Drive

AS

E5L0660ADC - 6 to 60mm Vari-focal DC Iris Lens, 1/3" Format

- F1.6 - 125
- CS Mount
- Ordering no. 64E5L0660ADC

ESLO50100ADC - 5 to 100mm Vari -focal DC Iris Lens ,1/3" Format

- F1.1.6
- CS Mount
- Ordering no. 64E5L05100ADC

PENTAX

HS2V616ED (DC) - 6 to 12mm Vari-focal DC Iris Lens, Day/Night, 1/2" Format

- F1.6 - 200
- CS Mount

TS2V114E (DC)* - 1.6 to 3.4mm Vari-focal DC is Lens,1/3" Format

- F1.4
- CS Mount
- *Please note that this product may subject to a 4 week lead time

TS2V214AED (DC) - 2.8 to 6mm Vari-focal DC Iris Lens, Day/Night, 1/3" Format*

- F1.4 - 200
- CS Mount
- *Please note that this product is subject to a 4 week lead time

TS2V314CED (DC) - 3.5 to 8mm Vari-focal DC Iris, Day/Night Lens, 1/3" Format

- F1.4 - 300
- CS Mount
- Ordering no. 59TS2V314CED

TS3V310ED (DC) - 3 to 8mm Vari-focal DC Iris Lens, Day/Night, 1/3" Format

- F1.4 - 300
- CS Mount
- Ordering no. 59TS3V310E-ED

TS4V214ED (DC)* - 2.8 to 12mm Vari-focal DC Iris Lens, 1/3" Format

- F1.4 - 200
- CS Mount
- Ordering no. 59TS4V214ED
- *Please note that this product may subject to a 4 week lead time

TSV10V518AED - 5 to 50mm Vari-focal DC Iris Lens, 1/3" Format

- F1:1.8 - 200
- CS Mount
- Ordering no. 59TS10V518E

Monitors
Colour

SAMSUNG

SMC-152FP - Samsung Electronics 15" Flat Colour Monitor

- 400TVL
- 4 x video & audio inputs
- 1 x video & audio output
- 220VAC
- Ordering no. 61SMC-152FP

SMC-213FP - 21" Flat Colour Monitor Slim

- 500 TVL
- 2 x video & audio Inputs
- 1 x video & audio output
- 220VAC
- Ordering no. 61SMC-210FP

VISIONLINE

VLM-15CH - 15" Colour Monitor

- 600 TVL
- 220 VAC
- Ordering no. 56VLM-15CH

TFT LCD

SAMSUNG

SMT-1721P - 17" TFT Colour LCD Monitor

- 2 x Video and Audio Inputs
- 1 x VGA Input
- 1 x S-VHS Input
- Includes 12 VDC Power Supply
- Ordering no. 61SMT-1721P

SMT-1921P* - 19" TFT Colour LCD Monitor

- 2 x Video and Audio Inputs
- 1 x VGA Input
- 1 x S-VHS Input
- Includes 12 VDC Power Supply
- Ordering no. 61SMT-1921P
- *This product is subject to a 4 week lead time

VISIONLINE

KS-ML1520 - 15" TFT Colour LCD Monitor

- AV in
- S-Video
- XGA (1024 x 768)
- On Screen Display (OSD) Control
- Includes a 12VDC Power Supply
- Ordering no. 56KS-ML1520

KS-ML1720 - VisionLine 17" TFT Colour LCD Monitor

- AV in
- S-Video/Audio
- XGA (1024 x 768)
- On Screen Display (OSD) Control
- Includes a 12VDC Power Supply
- Ordering no. 56KS-ML1720

KS-ML1920 - 19" TFT Colour LCD Monitor

- AV in
- S-Video/Audio
- XGA(1024 x 768)
- On Screen Display (OSD) control
- Includes 12VCD Power Supply
- Ordering no. 56KS-ML1920

Sequintial Switches

VISIONLINE

CCD-802C - Navigator 4-Way Sequential Switcher

- 4 Input Auto Switcher
- 4 Video / Audio Input
- Switching interval approx. 1 second to 30 seconds
- DC12V 600mA
- Includes power supply
- Includes remote
- Ordering no. 57CCD-802

VLS-4SW - 4 Channel Sequential Switcher

- Switching intervals 1 second - 45 seconds
- Channel switches: bypass, Auto, home
- 220VAC
- Ordering no. 70VLS-4SW

VLS-8SW - VisionLine 8 Channel Sequential Switcher

- Switching interval 1 second - 45 second
- Channel switches: bypass, auto, home
- 220VAC
- Ordering no. 70VLS-8SW

Embedded Digital Video Recorders

SAMSUNG

SHR-2160P - 16 Channel Duplex RealTime Digital Video/Audio Recorder

- MPEG4 Compression
- 4 x Audio
- 400 ips display
- 100 ips recording CIF, 50 ips Half D1
- 2 Composite monitor outputs
- LAN/ADSL
- 2 x USB 2.0 backup
- 160GB internal HD (up to 500GB)
- Ordering no.61SHR-2160P

SHR-4160P - 16 Channel Duplex RealTime Digital Video Recorder

- MPEG 4
- 8 x Audio
- 400ips display 1394 Backup
- 2 composite monitor outputs
- LAN/ADSL
- 2 x USB 2.0 & IEEE
- 120GB internal HD (expand up to 1TB)
- Ordering no.61SHR-4160P

SHR-5040P - 4 Channel Duplex RealTime Digital Video Recorder

- MPEG4 Compression
- 8 x Audio
- 400 ips display
- 2 Composite monitor outputs
- 200 ips recording CIF & 100 ips Half D1 & 50 ips D1
- LAN/ADSL
- 2 x USB 2.0 & IEEE 1394 Backup
- 160GB internal HD (expand up to 1TB)

- Ordering no.61SHR-5040P

SHR-5160P - 16 Channel Duplex RealTime Digital Video Recorder

- MPEG4 Compression
- 8 x Audio
- 480 ips display
- 2 Composite monitor outputs
- 120 ips recording CIF & 100 ips Halh DI & 50 ips D1
- 250 GB Hard disk
- CD-RW Drive
- USB Memory
- Ordering no.61SHR-5160P

VISIONLINE

HS-DM4060 - 4 Channel Standalone Network Digital Video Recorder

- Dual Functional
- Live Record / Play back / Backup / Internet
- 100 fps
- M JPEG & MPEG4 compression over Internet
- Supports TCP/IP, PPPoE, DHCP and DDNS
- Supported 2 x 750Gb Hard Disk
- Hard Disk readable in PC
- Excludes Hard Disk
- Ordering no. 56HS-DM4060

HS-DM4060VGA* - 4 Channel Standalone Network Digital Video Recorder with VGA Output

- Dual Functional
- Live Record / Play back / Backup / InternetVGA Output
- VGA Output
- 100 fps
- M JPEG & MPEG4 compression over Internet
- Supported 2 x 750Gb Hard Disk
- Hard Disk readable in PC
- Excludes Hard Disk
- *This product may subject to a 4 week lead time
- Ordering no. 56HS-DM4060VGA

HS-DM6030* - 8 Channel Standalone Network Digital Video Recorder

- Dual Functional
- Live Record / Play back / Backup / Internet
- 200 fps
- M JPEG & MPEG4 compression over Internet
- Supports TCP/IP, PPPoE, DHCP and DDNS
- Supported 2 x 750Gb Hard Disk
- Hard Disk readable in PC
- Excludes Hard Disk
- *This product may subject to a 4 week lead time
- Ordering no. 56-HS-DM6030

HS-DM8030* - 16 Channel Standalone Network Digital Video Recorder

- Dual Functional
- Live Record / Play back / Backup / Internet
- 400 fps
- M JPEG & MPEG4 compression over Internet
- Supports TCP/IP, PPPoE, DHCP and DDNS
- Supported 2 x 750Gb Hard Disk
- Hard Disk readable in PC

- Excludes Hard Disk
- *This product may subject to a 4 week lead time
- Ordering no. 56HS-8030

PC-Based Digital Video Recorders

SAMSUNG

SPR-7116P - 16 Channel PC Based Digital Video Recorder

- MPEG4 Compression
- Various resolutions can be set for monitoring or recording
- Hardware watchdog function
- Motion detection function
- 480 ips display
- 250 GB Hard disk
- CD-RW Drive
- USB Memory
- Ordering no. 61SPR-7116P

VISIONLINE

VL-Verifier16-160 - Verifier 16 Channel PC Based Digital Video Recorder

- 266ips Recording & Display
- SMICT compression
- USB and Ethernet
- 160GB HDD
- CD-RW
- 17" VGA Monitor with Keyboard & Mouse
- Audio
- Ordering no. 77VL-Verifier16-160

VL-Verifier4-160 - verifier 4 Channel PC Based Digital Video Recorder

- 50ips Recording & Display
- SMICT compression
- USB and Ethernet
- 160GB HDD
- CD-RW
- 17" VGA Monitor with Keyboard & Mouse
- Audio
- Ordering no. 77VLVERIFIER4-160

VL-Verifier8-160 - Verifier 8 Channel PC Based Digital Video Recorder

- 133ips Recording & Display
- SMICT compression
- USB and Ethernet
- 160GB HDD
- CD-RW
- 17" VGA Monitor with Keyboard & Mouse
- Audio
- Ordering no. 77VL-Verifier8-160

Plug & Play Video Capture Cards

AS

SecuWatch 32/ 64/ 128/ 256/ 512 - SecuWatch cameras version CMS

- Central Monitoring Multiple VPON Network DVR and Video
- 1/ 4/ 9/ 16/ 25/ 36/ 49/ 64 Split -Screen display support
- Maximum 256 cameras connections for live studio
- Up-to-64-camera grouping support
- Remote PTC camera control
- Cyclic recording to preset disk space or auto stop after space full
- E-map support with GPI/O control
- And many more

- Ordering no.74SECUWATCH-CMS

VP100 - 4 Channel Digital Video Card with Software

- Linux based system
- Plug & Record, no operation system needed, no virus system crash concern
- Watermark to prevent fraud image modification
- Adjustable recording frame rates and resolution for each camera
- Browser -based, no remote viewing software needed
- Access prohibition for pre-defined through IP-network
- Ordering no.74VP-100

VP101 - 4 Channel RealTime Digital Video Card with Software

- RealTime network DVR firmware in a DOM (disk on module
- Plug and play, no operating system required
- 4 Video input up to Full D1 resolution (720x480)
- Browser -based, no remote viewing software needed
- Live monitoring, up to 30 fps for each camera
- Simultaneously Record / Playback / Back-up/ browse capabilities
- Built-in web server and firewall
- Includes: 1 x DOM Chip, 1 x VP41 Card, 1 x IR Remote
- Ordering no.74VP101

VP102 - 8 Channel Digital Video Card with Software

- Network DVR firmware in a DOM (disk on Module)
- Adjustable recording frame rates and resolution for each camera
- Browser -based, no remote viewing software needed
- Access prohibition for pre-defined hosts through IP network
- Maximum 200 ips / system
- Ordering no. 74VP102

VP40 - 4 Video Channel Expansion Card for VP100

- Linux based system
- Plug & record, no operation system needed, no virus system crash concern
- Watermark to prevent fraud image modification
- Adjustable recording frame rates and resolution for each camera
- Access prohibition for pre-defined through IP- network
- Ordering no. 74VP40

VP41 - 4 Video Channel Expansion Card for VP101

- Linux based system
- Plug & record ,no operation system needed ,no virus system crash concern
- Watermark to prevent fraud image modification
- Adjustable recording frame rates and resolution for each camera
- Access prohibition for pre-defined through IP- network
- Ordering no. 74VP41

VP42 - 4 Video Channel Expansion Card for VP102

- Network DVR firmware in a DOM (disk on Module)
- Control well known brand PTZ cameras
- Adjustable recording frame rates and resolution for each camera
- Browser -based, no remote viewing software needed
- Access prohibition for pre-defined hosts through IP network
- Maximum 200 ips / system
- Ordering no. 74VP42

VP-DIO44 - For the Extent of I/O Port for VP-SIO44 Card or VP-41 DVR Card

- DI (input): 4 Inputs, Dry Connect (OPEN/SHORT)
- DI (input): 4 Inputs, Dry Connect (OPEN/SHORT)
- DO (output) Relay Resistive Load: 3A 120VAC, 3A 24VDC
- DO (output) Relay Max. Switching: 120VA, 60W, 120VAC, 30VDC, 2A
- Ordering no.74VP-DIO44

VP-DIO80 - For Extend of the I/O Port for VP-SIO44 Card

- DI (input): 4 Inputs, Dry Connect (OPEN/SHORT)
- Ordering no. 74VP-DIO80

VP-DIO84 - VP24 / 28 I/O card (8 In / 4 Out)

- DI (input):8 Inputs, Dry connect (OPEN/SHORT)
- DO (output): 4 Outputs, Normal Open (N.O.)
- DO (output) Relay Resistive Load:3A 120 VAC, 3A 24VDC
- DO (output) Relay Max. Switching: 120VA, 60W, 120VAC, 30VDC, 2A
- Ordering no.74VP-DIO84

VP-MB945G - Professional DVR Motherboard

- Based on Intel 945G Northbridge chipset and Intel
- Supports Intel Pentium Extreme Edition/ Pentium D/ Pentium 4/ Celeron D Processor
- Supports Dual Channel Technology and allows you installing a total memory capacity of 2 GB
- The main board comes with Serial ATA II connectors which the interfaces can provide the transmit rat
- VP-MB945G motherboard was designed for security applications and is best suited DVR machine assembly
- It has 4 PCI slots and 2 PCI-E connectors with built in RS-485and GPIO devices
- Ordering no.74VP-MB945G

VP-SIO44 - RS-485 with 4 Input / 4 Output PCI Card

- RS-485 with 4 input / 4 output PC card
- Ordering no.74VP-SIO44

EX9060 - GPI/O 4 Input / 4 Out module

- Ordering no.74EX9060

EX9520 - RS232 to RS422/485 Converter

- Ordering no.74EX9520

PC Starter Kit - Midi Tower PC Starter Kit

- Includes:
- VP-MB865 ATX Motherboard
- Pentium IV 3.0 GHz Processor
- 512Mb Memory
- Optional mouse & keyboard
- Ordering no. 74PCVPONKit

PC Starter Kit-Pro - Professional Midi Tower PC Starter Kit

- Includes
- VP-MB954G ATX Motherboard
- Pentium IV 3.0 GHz Processor
- 512Mb Memory
- Optional mouse & keyboard
- Ordering no.74PCVPONKIT-PRO

UDVR4 - 4 Channel USB Video Capture Card Unit with Software

- Simply plug into any PC* and start recording
- 25 ips
- MPEG4 Software compression
- 320 x 240 Resolution
- Network Interface
- Ordering no. 84UDVR4
- *Subject to computer specifications

VG4C-RT4 - Verifier 4 Channel RealTime Digital Video Card with Software

- 100 ips (25 fps/channel)
- 4 x Audio Channels
- Ordering no. 62VG4C-RT4

VG4C-XP - Verifier 4 Channel Digital Video Card with Software

- 50ips (12.5 fps/channel)
- 2 x Audio Channels
- Ordering no. 62VG4C-XP

VG8C-RT4 - Verifier 8 Channel RealTime Digital Video Card with Software

- 200 ips (25 fps/channel)
- 8 x Audio Channels
- 1 x Composite out
- Ordering no. 62VG8C-RT4

VG8C-XP-TV - Verifier 8 Channel Digital Video Card with Software

- 133ips (16.6 fps/channel)
- 2 x Audio Channels
- 1 x Composite out
- Ordering no. 62VG8C-XP-TV

Mobile Digital video Recording

VISIONLINE

CR-246 - 1/4" IR Rear View Camera for On-the-Road Application

- 3.6mm lens
- 380 TVL
- 12 VDC

CR-247 - 1/4" IR Rear View Camera for On-the-Road Application

- 3.6mm lens
- 480 TVL
- 12 VDC

CR-B248SY - 1/3" IR Rear View Camera for On-the-Road Application

- 3.6mm lens
- 400 TVL
- 0.1 Lux
- 12 VDC

DVR-M104H - MobiTech 4 Channel Digital Video Multiplexer / Recorder

- 4 video and 1 audio input
- 30 fps in DVR-M104H
- Digital video images stored in a 2.5" hard drive
- Supports LAN/ GPRS/ CDMA/ WI-FI interface
- Compact Flash Memory served as backup with incident or continuous storage
- Anti-Vibration : 1G ; 5-500Hz
- 12 Volt DC
- Ordering no. 90DVR-M104H

DVR-M208 - MobiTech 8 Channel Digital Video Multiplexer/Recorder

- 8 video and 2 audio input
- 60 fps in DVR-M208
- MPEG4 / MJPEG
- Digital video images stored in a 2.5" hard drive
- Supports LAN/ GPRS/ CDMA/ WI-FI interface
- Compact Flash Memory served as backup with incident or continuous storage
- Anti-Vibration : 1G ; 5-500Hz
- 12 Volt DC
- Ordering no. 90DVR-M208H

H203 - GPS Modem

- General: L1 Frequency
- C/A codes
- 12-channel
- Sensitivity: -165 dBW minimum
- Update Rate: 1 Hz
- Accuracy: Position:25m CEP without S/A
- Ordering no. 90DVR-M208-H203

MG32 - GSM/GPRS Modem

- Tri-Band
- GSM900/ DCS1800/ PCS1900
- High performance and compact design
- Supports GSM data
- Voice, fax and SMS
- Ordering no. 90DVR-M208-MG-32

HS-A01 - Single Channel Video Amplifier

- For B/W or Colour Cameras
- 110 or 230VAC
- Ordering no. 56HS-A01

Twisted pair Cable Transmission

VISIONLINE

VLC-TTA111VR - Single Channel Active Twisted Pair Video Transmitter

- Maximum 1.8 km
- 12 volt DC
- Ordering no. 62VLC-TTA111VR

VLC-TTA111VT - Single Channel Active Twisted Pair Video Transmitter

- Maximum 1.8 km
- 12 volt DC
- Ordering no. 62VLC-TTA111VT

VLC-TTA414VR - 4 Channel Active Twisted Pair Video Receiver

- Maximum 1.8 km
- 12 volt DC
- Ordering no. 62VLC-TTA414VR

VLC-TTP111V - Single Channel Passive Twisted Pair Video Transceiver

- Maximum 600 meters
- Ordering no. 62VLC-TTP111V

VLC-TTP414V - 4 Channel Passive Twisted Pair Video Transceiver

- Maximum 600 meters
- Ordering no. 62VLC-TTP414V

Web Transmitters / Receivers / Decoder

SAMSUNG

SNS-110P - Samsung Electronics 4 x Video Web Transmitter

- Remote monitoring at the various network environment 10/100Base T Ethernet, Cable network, ADSL (Static ip)
- Checks and monitors remote places connected with internet or intranet remote connection using a standard web browser such as Explorer
- Send e-mail once the alarm turns on (to maximum 5 users)
- Transfer the captured images to a assigned FTP server at the alarm event
- 10/100BaseT Ethernet
- Ordering no. 61SNS-110P

Camera Brackets

VISIONLINE

TS-B12 - Aluminum 165mm Mini I-type Bracket with 360 degree Swivel

- For outdoor applications
- Dimension 275x99x83 (mm)
- Ordering no. 70TS-B12

TS-B13 - Wall or Ceiling Mount PVC 165mm Mini Bracket

- PVC 165mm Mini bracket
- For indoor applications
- Ordering no. 70TS-B13

TS-B20 - Aluminum 285mm Mounting Bracket

- Dimension 275 x 99 x 83 (mm)
- Ordering no. 70TS-B20

Camera Housings

VISIONLINE

TS-H11 - Outdoor Aluminum Camera Housing with Sun Shield & Heater

- Internal dimension
- Dimension 145 x 135 x 470 (mm)
- Ordering no. 70TS-H11

TS-H12 - Outdoor Aluminum Camera Housing with Sun Shield

- Dimension 410 x 118 x 113 (mm)
- Ordering no. 70TS-H12

TS-H5 - Outdoor Aluminum Camera Housing with Sun Shield

- 89(W) x 92(H) x 265(L)mm
- Ordering no. 70TS-H5

TS-H7 - Outdoor Aluminum Camera Housing with Sun Shield

- 89(W) x 92(H) x 310(L)mm
- Ordering no. 70TS-H7

Lighting Protection

VISIONLINE

LPC02 - Inline Video Lightning and Surge Protector

- 1 ns surge protector attach time
- Maximum 4 kv surge voltage
- 300 surges at 100amps surge life
- Ordering no. 77LPC

Visual Verification

OZVISION

OzLine 4CS - Remote Video System

- Supports up to four video sources
- Built-in modem
- Video transmission over standard phone lines
- Built-in switcher for on-site monitoring and recording
- RAM for recording and transmitting pre-alarm and post-alarm activity
- Four relay outputs for remote activation of devices (lights, speakers)
- Transmits over cellular telephone networks
- Includes software and instructions
- Compatible with Central Station infrastructure
- Look-in capability
- Order No. OzLine 4CS